

iGLO LED UFO High Bay - 400W

ENVIRONMENTALLY FRIENDLY, ENERGY EFFICIENT

iGLOLED
IGLOLED.NET



Features

- DLC Premium and cULus Certificates
- Low-profile design
- Up to 145 LPW ultra-high efficiency delivers superior performance over older HID high bays
- 0-10V dimming
- Instant-on with no warm-up
- Quick/Easy to install and operate.
- IP65 Rated for dust and high pressure water ingress protection
- UL Listed for wet locations
- Impact resistant polycarbonate lens
- Slim, lightweight die-cast aluminum construction





Applications



- Warehouses
- Manufacturing Plants
- Distribution Centers
- Grocery Stores
- Gymnasiums
- Indoor Recreational Facilities
- Cold Storage
- Big Box Retail
- Service Repair Centers



Pendent



Surface-mounted




PRODUCT SPECIFICATIONS

Product Code	GL400WUFOAST-5K				
DLC Listing	AST-HB11-400WS1BT2H1-abcd				
Wattage	400W				
Replaces	1500W Metal Halide				
Input Voltage and Frequency	100-277VAC, 50/60Hz				
Dimming	0-10V dimming standard				
Color Temperature	3500K	4000K	4500K	5000K	5700K
Lumens	53200 LM	55200LM	56400LM	56400LM	56800LM
Efficacy	133 LM/W	138LM/W	141LM/W	141LM/W	142LM/W
CRI	>8				
PF	≥0.9				
THD	≤20%				
Beam Angle	90 Degree				
Optional Accessory	Motion Sensor, Surge-protective Device				
Driver Surge protection	L-N: 10kV, L/N-PE: 6kV				
Operating Temperature	Without Motion Sensor: -40℃ TO 50℃				
	With Motion Sensor: -30℃ TO 50℃				
Housing	Die-cast aluminum				
Housing Color	Black, White, or Customized				
Waterproof Rating	WET (IP65)				
Warranty	5 years warranty				

SHIPPING

Lamp Type	Carton Size	Qty / Carton	Net Weight / Carton	Gross Weight / Carton
Pendent	510*510*230mm	1 PC	6.9KG	8.3KG
Surface-mounted	510*510*230mm	1 PC	9KG	10.4KG

DIMENSIONS



PHOTOMETRIC DATA

CIE Class: Direct

Measurement Flux: 53370.1 lm

Downward Ratio: 100%

Field Angle(C0/C180,C90/C270,C45/C225,C135/315): 125.1, 123.1, 123.1, 126.0

Beam Angle(C0/C180,C90/C270,C45/C225,C135/315): 85.1, 83.5, 85.6, 84.1

Luminaire Efficacy Rating (LER): 134.84

Max. Intensity: 27769.41 cd

S/MH(C0/C180): 1.38

Total Rated Lamp Lumens: 53370.1 lm

Efficiency: 100%


Upward Ratio: 0%

C0r0 Intensity: 26504.47 cd



Pos of Max. Intensity: H67.5 V26

S/MH(C90/C270): 1.33

Luminous Intensity Distribution Curve



The Average Illuminance Effective Figure



Disclaimer

This product data sheet provides periodic information, and the content can be updated at any time according to the actual situation of the product without notice. If caused by improper use of this product data sheet The company does not assume any responsibility for direct or indirect losses

